

ARCHITECTURAL PAVER TILE

PRODUCT DESCRIPTION



Protect Yourself.... Protect your Investment

- High Density and extremely durable yet shock absorbing providing more comfort underfoot than traditional hardscape
- Manufactured from 100% post consumer waste tires





BENEFITS:

- Easy to Install modular design allows fully adhered or floating applications
- *Safe* non-toxic and steel free with a slip resistant surface whether wet or dry
- Easy to Maintain requires only basic cleaning with a broom, vacuum or hose
- Attractive available with a Flat Top or Brick Top pattern

Go GREEN





1 (888) 836-2665





ARCHITECTURAL PAVER TILE

TECHNICAL DATA



Description

Paver Tiles are a 1/2" or 3/4" thick resilient and skid resistant rubber tile surfacing alternative to traditional commercial flooring materials.

Paver Tiles are manufactured from 100% post-consumer California waste tires and provide an exceptionally durable, safe, low maintenance option to bare concrete or other hard surface materials.



Standard Colors

MEMBER

Uses


Paver Tiles are ideally suited to improve the beauty, comfort and ease of maintenance in various environments including fitness centers, shopping malls, daycare centers, churches, walkways, garages and even around swimming pools.



Advantages



Paver Tiles are exceptionally durable and resilient and provide years of performance.



- Paver Tiles are environmentally friendly, molded from 100% California recycled waste tires diverting as many as 2.5 tires per tile from our landfills.
- Paver Tiles are safe containing no toxic materials and certified to be 99.9% steel free.
- Paver Tiles have a very smooth top surface providing comfort to bare feet, hands and elbows while maintaining exceptional skid resistance whether wet or dry.
- Paver Tiles absorb shock making them more comfortable to walk on than traditional hardscape materials.



- Paver Tiles are modular in design making them easy to install over the largest selection of sub-grades including concrete, asphalt, wood decking and compacted gravel.
- Paver Tiles are easy to maintain requiring only basic cleaning with a broom, vacuum or water hose on a regular basis.
- Paver Tiles come in a variety of colors providing a multitude of design options to meet any need.
- Paver Tiles are backed by the industries leading manufacturer of rubber molded safety tiles and accessories and come with a 5 Year Limited Material Warranty.

Product Specification

24" x 24" ± 1/8" Tile Size: Tile Thickness: 1/2", 3/4" Tile Weight: 9lb, 12.75lb

Physical Properties

Characteristic	Test	Result
Flame Spread:	ASTM E108	Class A
Flammability:	ASTM E648	Class II
Flammability:	ASTM 2859	Pass
Toxicity:	ASTM 2075	Lead Free
Slip Resistance:	ASTM F1677	Dry 0.63, Wet .052
Skid Resistance:	ASTM E303	Dry 96, Wet 47
Tensile Strength:	ASTM D412	1175.3 psi
Wear Resistance:	ASTM D3884	1.64% Loss/3000c
UV Resistances:	QPanel QUV	<3.0/4032 ksqm

Finish Options

Paver Tiles are available in Flat Top or Brick Top patterns in 11 standard colors. (Brick Top only available in 3/4")



Red Black

Blue Black

Tan Black